




Nano Coating
Prevent germs and bacteria
Ease of cleaning



Tool-free SSD Access
Ease of installation
Reduced risk of misplacement



Concealed Ports
Improved cable management
Protection against dust and debris

Internal Power Supply



IP66 Whole Unit
Reduced risk of electrical failures
Longer equipment lifespan

Distributed/Imported Exclusively by MachX Enterprise

MachX Enterprise

- +61 7 3275 5855















Specifications

Intel Quad Core Celeron J6412 2.0 GHz up to 2.6 GHz

System Memory 8 GB DDR4 RAM (up to 16 GB) 1 x removable 128 GB M.2 2280 SSD Storage

KDS X3220

Intel Core i3-7020U 2.3 GHz

8 GB DDR4 RAM (up to 16 GB) 1x removable 128 GB M.2 2280 SSD

Display

21.5" TFT LCD (LED backlight) Size

Resolution 1920 x 1080 pixels **Brightness** 250 cd/m2

KDS J64

Touch Screen Panel Projected capacitive touch (multi-touch) 21.5" TFT LCD (LED backlight)

1920 x 1080 pixels

250 cd/m2

Projected capacitive touch (multi-touch)

I/O Interface

USB Port 3 x USB 2.0, 1 x USB 3.0 3 x USB 2.0, 1 x USB 3.0

Serial Port 3 x RJ50 3 x RJ50

Network Port 1x RJ45 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Cash Drawer Port 1 x RJ12 (supports both 12 V & 24 V) 1x RJ12 (supports both 12 V & 24 V)

Video & Audio Port 1x HDMI 1x HDMI Speaker 2 x 2 W 2 x 2 W

Operating System

10 loT / 10 Pro / 11 10 loT / 10 Pro / 11

Environment & Mechanical

519 (W) x 322 (H) x 46 (D) mm | 8.0 kg **Dimensions & Weight**

Heat-dissipating solid aluminium die-cast casing Chassis Material

VESA Pattern 100 x 100 mm Safety Certification & IP Rating IP66 compliant

Operating: 0°C to 60°C | Storage: -20°C to 60°C Temperature

Humidity Relative: 10% to 90% (non-condensing)

Power Consumption DC output: 19 V / 5 A | 65 W | AC input: 100 V to 240 V

Model Options

Integrated Wi-Fi 802.11 b/g/n/ac

All product specifications are subject to change without notice.

MachX Enterprise

67 Weaver Street Coopers Plains QLD 4108, Australia

+61 7 3275 5855

