

HPC X10W

Rugged Tablet PC



SE^NOR



Ergonomic Handstrap

Reduces risk of drops
Enhances comfort for extended use



2D Scanner & Comprehensive Charging Dock

Optional



Rugged Design

1.22m Drop Test
IP65 Whole Unit



Hot Swap Battery

Allows continuous device use
Removes charging downtime

Distributed/Imported Exclusively by MachX Enterprise

MachX Enterprise

📍 67 Weaver Street Coopers Plains QLD 4108, Australia

☎ +61 7 3275 5855

✉ sales@machx.com.au

🌐 www.machx.com.au

MACHX



Specifications

	HPC X10W N5	HPC X10W T5	HPC X10W T7
Processor	Intel Celeron N5105 2.0 GHz (up to 2.9 GHz)	Intel Core i5-1235U (up to 4.4 GHz)	Intel Core i7-1255U (up to 4.7 GHz)
System Memory	8 GB RAM (up to 16 GB)	16 GB RAM	16 GB RAM
Storage	1 x 128 GB removable M.2 NVMe 2280 SSD		

Display

Size / Resolution	10.1" IPS LCD / 1920 x 1200 pixels		
Brightness	700 cd/m ²		
Touch Screen Panel	Projected capacitive touch (10-point G+G)		

I/O Interface

USB Port	1 x USB 3.0 Type-A 1 x USB Type-C	1 x USB 3.1 Type-A 1 x USB Type-C	1 x USB 3.1 Type-A 1 x USB Type-C
WWAN SIM Card	LTE FDD: B1/B3/B7/B8/B20 LTE TDD: B40 GSM: 900/1800	LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B40 GSM: 900/1800	LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B40 GSM: 900/1800
Wi-Fi & Bluetooth	Wi-Fi 802.11 a/b/g/n/ac (2.4G/5.8G) Bluetooth 5.0	Wi-Fi 6 802.11 a/b/d/e/g/h/i/k/n/r/u/v/w/ac/ax (2.4G/5.8G) Bluetooth 5.1	
Audio	3.5 mm jack	3.5 mm jack	3.5 mm jack
Video	1 x Mini HDMI 2.0a	1 x Mini HDMI 2.1a	1 x Mini HDMI 2.1a

Operating System

Windows	11 IoT / 11 Pro	10 (optional) / 11	10 (optional) / 11
---------	-----------------	--------------------	--------------------

Environment & Mechanical

Dimensions & Weight	290 (W) x 197 (H) x 28 (D) mm 1140 g		
Battery	1 x built-in battery: 700 mAh 1 x removable battery: 5000 mAh (4.5 hours)		
Cameras	Front: 5.0 MP Rear: 8.0 MP		
Sensors	GPS, GLONASS		
IP Rating & Drop Test	IP65 whole unit 1.22 M MIL-STD-810G certified		
Temperature	Operating: -20°C to 60°C Storage: -30°C to 70°C		
Humidity	Operating: RH95% (non-condensing)		
Power Consumption	19 V / 3.42 A, internal power adaptor, 100-240 V, 50/60 Hz		

Model Options

Charging Dock	2 x USB, 1 x Serial, 1 x LAN, supports tablet & battery charging
Vehicle Mount	1 x RS232, 1 x RJ45, 1 x USB, 1 x DC, with VESA pattern and key lock
RFID	13.56 MHz (NFC)
Biometric security	Fingerprint reader
Expansion Port	Choose 1 from 2D scanner / serial port / LAN port / USB 2.0 port

All product specifications are subject to change without notice.

MachX Enterprise

 67 Weaver Street Coopers Plains QLD 4108, Australia
 +61 7 3275 5855  sales@machx.com.au
 www.machx.com.au

