

# XPC N10W

## Explosion-proof Rugged Tablet PC



SE/MOR



**ATEX 2/22 Zone  
Explosion-proof  
Certification**



**Sunlight Readable Display**  
High brightness LCD up to 700 nits#  
Clear visibility in sunlight



**Removable Battery**  
UN38.3 / IEC62133  
safety standard 5,000 mAh  
8 hours operating time\*



**Rugged Design**  
IP65 whole unit  
MIL-STD-810G certified

# Optional \* Under normal usage

**Distributed/Imported Exclusively by MachX Enterprise**

**MachX Enterprise**

📍 67 Weaver Street Coopers Plains QLD 4108, Australia

☎ +61 7 3275 5855

✉ sales@machx.com.au

🌐 www.machx.com.au

**MACHX**

# Product View





## Specifications

Processor	Intel Celeron Quad Core N5100 1.10 GHz (up to 2.80 GHz)
System Memory	8 GB RAM
Storage	128 GB eMMC

## Display

Size, Resolution, & Brightness	10.1" TFT LCD / 1920 x 1200 pixels, 400 cd/m <sup>2</sup> (optional 1280 x 800 pixels, 700 cd/m <sup>2</sup> )
Touch Screen Panel	Projected capacitive touch (10-point)

## I/O Interface

USB Port	1 x USB 3.0 Type-A, 1 x USB 3.1 Type-C
Expansion Port	1 x RJ45 LAN (10/100 Mbps) or 1 x DB9 Serial (RS232) or 1 x USB 2.0 Type-A
WWAN   SIM Card	LTE FDD: B1/B3/B7/B8/B20   LTE-TDD: B40   WCDMA: B1/B5/B8   GSM: B3/B8   1 x SIM, 1 x TF Card
Sensors	GPS, Glonass
Wi-Fi & Bluetooth	Wi-Fi 802.11 a/b/g/n/ac 2.4 GHz & 5 GHz, Bluetooth 5.0
Audio	2 x 1 W speaker, ø 3.5 mm jack
Video	1 x Mini HDMI 2.0a
Cameras	Front: 5.0 MP   Rear: 8 MP

## Operating System

Windows	10 Pro / 11 Pro
---------	-----------------

## Environment & Mechanical

Dimensions & Weight	274.9 (W) x 188.7 (H) x 23.1 (D) mm   1140 g
Battery	UN38.3, IEC62133 5,000 mAh removable (up to 8 hours operating time)
IP Rating & Drop Test	IP65 whole unit   MIL-STD-810H certified (1.2 M on plywood)
Explosion-proof	ATEX 2/22 Zone, II 3G Ex ic op is IIC T4 Gc, II 3D Ex ic op is IIB T130°C Dc
Temperature	Operating: -20°C to 60°C   Storage: -30°C to 70°C
Humidity	Operating: 95% (non-condensing)   Storage: 95% (non-condensing)
Power Consumption	Power adaptor input: AC 100-240 V, 50/60 Hz Power adaptor output: DC 12V/4A

## Optional Data Collection

2D Scanner	Honeywell N3680 1D / 2D barcode reader
NFC	13.56MHz, Support ISO/IEC 14443A/B/15693/18092/mifare protocols Card reading distance: 4 cm

## Accessories



Hand-strap



12V/4A Adaptor



Docking Charger



Vehicle Mount



Car Charger



Back-strap



TP Resist Film



Quad Charging

All product specifications are subject to change without notice.

## MachX Enterprise

67 Weaver Street Coopers Plains QLD 4108, Australia

+61 7 3275 5855

sales@machx.com.au

www.machx.com.au

